



SIZE	A	B	C	D	L0	d0	H	L	D1	N-M	&°	ISO5211	K	F	4-φd	F	G
2"	140	80	42	56.4	225	14.3	11	32	125	4-16	90	F07	90	70	4-10	55.25	4
2.5"	152	89	45.8	68.27	266	14.3	11	32	145	4-16	90	F07	90	70	4-10	55.25	4
3"	159	95	45.8	80.9	266	14.3	11	32	160	8-16	45	F07	90	70	4-10	55.25	4
4"	178	114	52	106.5	266	15.77	11	32	180	8-16	45	F07	90	70	4-10	55.25	4
5"	191	127	55	131.4	266	18.92	14	32	210	8-16	45	F07	90	70	4-10	55.25	4
6"	204	139	55.8	153.4	266	18.92	14	32	240	8-20	45	F07	90	70	4-10	55.25	4

NO.	PARTS NAME	MATERIAL	QTY	TEST PRESSURE	
				SHELL	SEAL
9	LEVER	Cast Iron	1		
8	INDICATOR	CARBON STEEL	1		
7	O-RING	EPDM	1		
6	BUSHING	P.T.F.E.	4		
5	STEM	SS304	1		
4	SEAT	EPDM	1		
3	PN	316 SS	2		ONLY 2.5" ONE PIN
2	DISC	SS316	1		
1	BODY	GGG40	1		

STAND-ARD	DESIGN CODE	BS 5155
	INSPECTION & TEST	DIN 3230 PART 3
	END STANDARD	DIN PN16
	FACE TO FACE	DIN 3202 K1

HYDROSTATIC	24 kg/cm ²	17.6 kg/cm ²
AIR		

TITLE : LEVER LUG BUTTERFLY VALVE
 DNS50-DN150

APPROVED	DWG NO.	REV
CHECKED		
DRAWN		
DESIGNED	SCALE	UNIT
		mm